

CHIBA Fire Shark (Item No. 61214)



Description:

Finger glove **Carbon X[®]** for maximum protection even under extreme conditions.
The palm made of leather provides an excellent tactile feel and very good traction and grip even on wet surfaces.
Lining with cut-resistant insulation material made of a Kevlar[®] -Glassfibre-mixture for highest cut protection (level 5) and at the same time the best insulation.
Additional isolation of the glove with 100% para-aramid felt.
The glove is fitted with a waterproof and breathable Eurotex[®]-membrane. Perfect fit by elastic contraction on the wrist. Highest ankle protection with a silicone protector and palm protection, sewn-in elastic band. 3M[®] reflective stripes for better visibility in the dark. Strong pre-curved fingers for a perfect fit
All seams are made with Kevlar[®]-thread.

Sizes:	7-13
Colour:	black
Length:	about 30 cm

Materials:

Palm Hand:	Leather, special double-face fabric with silicone coating
Top Hand:	Carbon X [®]
Cuff:	Carbon X [®]
Lining:	Double-face fabric made of 43% Aramid, 37% Polyester, 20% Glass-fibre Kevlar [®] -felt 100% Para-Aramid
Membrane:	Eurotex [®]
Material-composition	Shell: 60% Leather, 15% Aramid, 14% Polyacryl, 9% Polyamid, 1% Polyester, 1% Carbon Fibre Lining: 66% Aramid, 22% Polyester, 12% Glasfibre

User Information:

Washing:	Superficial pollution can be removed by brushing. Min 5 x washable up to 60°C
Storage:	The glove should be stored in a cool, dark and dry environment at a normal room temperature.
Limitations:	For special firefighting (entering fire or fire approach) other, special gloves (e.g according to EN 1486) are required. After mechanical or thermal stress the glove has to be checked for damage. Superficial damage by abrasion, sharp or edged objects, by heat and high pollution affect the protective effect. Protective gloves with such or similar damages have to be sorted out

Pictogram and performance levels according to EN 659:2003+A1:2008

Certificate No.: 72347		Results	LS	Notified Body: 0534 Österreichisches Textil- Forschungsinstitut, ÖTI Sprengergasse 20 A-1050 Wien
		Abrasion	3	
		Cut resistance	5	
		Tear resistance	4	
		Puncture resistance	3	
		Burn behavior	4	
		Dexterity	3	

Manufacturer:	CHIBA Gloves Germany GmbH & Co. KG Tragmoos 19 83317 Teisendorf Deutschland Tel. +49 (0)8666-9856-0 Fax. +49 (0)8666-9856-10 www.chiba.de - info@chiba.de
----------------------	-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------



شرکت ایمن سازان محیا تهران ۱۲۵ وارد کننده تجهیزات تخصصی ایمنی و آتش نشانی

برگزاری ۰۹۱۲۲۷۰۰۶۴۴
فانم ۰۹۱۲۵۲۴۹۵۵۰

۰۲۱۶۶۴۵۳۹۶۳-۰۲۱۶۶۴۵۳۹۶۵